SMART-RC-RGBW Receiver installation instructions

Warnings:

Do not connect the power source until all other connections are made.

Do not expose the unit to moisture

Wiring RGBW:

Wire the receiver to the light according to the R G B W lettering on the right of the receiver. The V+ (black) wires from the light must be put into the 'LED +' terminal.

To connect this, push down on the lever at the back of the terminal, push the wire into the gap/hole until it makes contact, then release the lever to close the terminal.

Connect the input power from your transformer to the correct terminals as labelled on the receiver.

Pairing to Phillips Hue:

- 1. Setup strip and Smart Home receiver, following the SMART-RC-Music instructions.
 - Connect to power and turn on.
- 2. In Phillips Hue App

Settings (Bottom right)

Devices

Add Light (Top left)

Select Room

'No QR Code'

'Next'

'Lights and smart plugs'

'Next

The lights connected to the receiver will flash twice to show successful pairing.

The new receiver will be added to the room.

(If no lights connect to the app please reset the receiver)

Fault finding:

If none of the lights are working, check that the power input wires are making contact (if not, strip wire cover back enough to ensure contact), including the positive wire for the LED.

If a single colour is not working, check that the wire is stripped back enough to make contact.

Connect the input power from your transformer to the correct terminals as labelled on the receiver (top left in above image).

To reset SM-RC:

Pulse the power to the receivers **five** times. The lights will flash to show it has been reset.

sales@sled.co.nz · sled.co.nz · 09 420 3160

Innovative Lighting Solutions

