




Tool-free fast wiring



Ordering Codes:	TPO1-1-28-O	28 Watts	623mm x 78mm	3,500 Lumens
	TPO1-1-56-O	56 Watts	1223mm x 78mm	7,000 Lumens
	TPO1-1-84-O	84 Watts	1823mm x 78mm	10,500 Lumens
IP Rating:	IP69K & IP66			
IK Rating:	IK10			
Materials:	Macrolon polycarbonate external construction. Can be used in areas that are hazardous to metal. Opal or frosted lens.			
Description:	<p>A removable centre piece with Quick Connect connectors allows easy change of power cable without affecting the internal sealing of the fitting.</p> <p>A removable gland takes 20mm conduit directly into the fitting.</p> <p>A filtered breather hole at one end aids cooling of the LED while also keeping the interior clean. It is pre wired at the other end with Quick Connect connectors to quickly and easily link the fitting into loop wiring, without affecting the IP rating or allowing dust intrusion into the main housing. Supplied as a standard surface mounted fitting.</p> <p>Suspension kits are also available.</p> <p>End cap with gland for easy conversion for series wiring is sold separately.</p>			
Operating Temperature:	-30°C to 50°C			
Applications:	Poultry sheds, agriculture, plant rooms, industrial freezer/cool room			
Control Systems:	Can be manufactured to suit a variety of control systems including Dali dimming. Emergency lighting versions available to order.			
LED Colours:	5500K White, 4000K Natural White, & 3000K Warm White			
Beam Angle:	Yes. Please specify when ordering.			
Standards:	Meets New Zealand and Australian electrical standards and has SAA approval.			
Warranty:	4 Years			