



| | | | | |
|------------------------|--|----------|---------------|---------------|
| Ordering Codes: | TPO1-3-28-O | 28 Watts | 623mm x 78mm | 3,500 Lumens |
| | TPO1-3-56-O | 56 Watts | 1223mm x 78mm | 7,000 Lumens |
| | TPO1-3-84-O | 84 Watts | 1823mm x 78mm | 10,500 Lumens |
| IP Rating: | IP69K & IP66 | | | |
| IK Rating: | IK10 | | | |
| Materials: | Macrolon polycarbonate external construction. Can be used in areas that are hazardous to metal. Opal or frosted lens. | | | |
| Description: | <p>A removable centre piece with Quick Connect connectors allows easy change of power cable without affecting the internal sealing of the fitting.</p> <p>A removable gland takes 20mm conduit directly into the fitting.</p> <p>A filtered breather hole at one end aids cooling of the LED while also keeping the interior clean. It is pre wired at the other end with Quick Connect connectors to quickly and easily link the fitting into loop wiring, without affecting the IP rating or allowing dust intrusion into the main housing. Supplied as a standard surface mounted fitting.</p> <p>Suspension kits are also available.</p> <p>End cap with gland for easy conversion for series wiring is sold separately.</p> | | | |
| Operating Temperature: | -30°C to 50°C | | | |
| Applications: | Poultry sheds, agriculture, plant rooms, industrial freezer/cool room | | | |
| Control Systems: | Can be manufactured to suit a variety of control systems including Dali dimming. Emergency lighting versions available to order. | | | |
| LED Colours: | 5500K White, 4000K Natural White, & 3000K Warm White | | | |
| Beam Angle: | Yes. Please specify when ordering. | | | |
| Standards: | Meets New Zealand and Australian electrical standards and has SAA approval. Complies to As/NZs 2293.3 2005. | | | |
| Warranty: | 4 Years | | | |